

S-4180-GX+

MULTI SATELLITE DUAL SATELLITE 8-WAY

4 LNBF and one UHF/VHF inputs and 8 outputs. For use with DIRECTV elliptical dish dual or triple satellite systems. Can be used with S-5040Y-CE to extend to 8 receivers.

Model Number	S-4180-GX+
Frequency Range	
Satellite	950 – 2200 MHz
Off-air	54 – 806 MHz
Satellite	
Insertion Loss / Gain	-2 to +5 dB
Same Sat. Cross-Pol. Isolation	30 dB
Diff. Sat. Cross-Pol Isolation	35 dB
Selection Control Voltage	
18V (101 LHCP)	16.75 – 21VDC
13V (101 RHCP)	11.75 – 14VDC
18V 22kHz (119 LHCP + 110	16.75 – 21VDC, w 22kHz
13V 22kHz (119 RHCP)	11.75 – 14VDC, w 22kHz
Off-air	
Insertion Loss	5 dB
Others	
Output Ports	8
Indoor or Outdoor	Indoor
22kHz Tone Output at 18V/22kHz and 13V/22kHz	Yes
DC Adapter Requirement	Required
Dimensions	8.5" x 3.75" x 1"
DC Adapter	
AC Input	115 VAC
DC Output Voltage	24 VDC
Max DC Current	1000 mA

